



**THE WORLDWIDE
DIVING STANDARD**

VIKING™ VALVES & HOSES



Viking Standard Inlet Valve.



Viking Push-Protected Inlet Valve.



Viking Hazmat Inlet Valve.



Viking Low-Acoustic Inlet Valve.

To provide the best possible solution for every diver and task faced, Viking offers a vast range of inlet and outlet valve models. All of them with the same high quality and reliability characterized by what is Viking.

VIKING STANDARD INLET VALVE

360° swiveling with an airflow of 80 liters/min. Available in a non-magnetic version fulfilling the requirements according to STANAG EOD operations. Fitted as standard on Viking PRO and HD.

VIKING PUSH-PROTECTED INLET VALVE

The actual button is lowered and protected by the surrounding housing to prevent accidental inflation by for example equipment strapping. 360° swiveling with an airflow of 80 liters/min. Fitted as standard on Viking COMBAT, PROTECH and HAZMAT.

VIKING HAZMAT INLET VALVE

Specifically developed for contaminated water diving. Equipped with an extra slide valve, to enable the diver to shut off the airflow in an emergency situation and thereby avoid the need to disconnect the hose and have contaminated water leaking through the inlet valve.

360° swiveling with an airflow of 80 liters/min open and 0 liters/min in shut-off position. Made from highly chemical resistant material. Available in a non-magnetic version fulfilling the requirements according to STANAG EOD operations.

VIKING LOW-ACOUSTIC INLET VALVE

Same design as the Hazmat Inlet Valve but with a different setting of slide valve functions. Fully open it has an airflow of 80 liters/min. In the "second" position the airflow is reduced to only 20 liters/min, thereby creating a significantly lower acoustic profile. Intended for military divers and only available in a non-magnetic version.



**THE WORLDWIDE
DIVING STANDARD**

VIKING™ VALVES & HOSES



Viking Standard Exhaust Valve (inset shows the non-magnetic version).



Viking Low-Profile Exhaust Valve.



Viking X2 Exhaust Valve.



Viking standard hose for inlet valves (inset shows the non-magnetic version).



Viking Chemical Protection.

VIKING STANDARD EXHAUST VALVE

Equipped with a rotating cap for adjustment of outgoing airflow. Turn valve towards "+" to let air out easily respectively "-" to let air out only by pushing down on the valve. Fitted as standard on Viking PRO and HD.

Also available in a non-magnetic version fulfilling the requirements according to STANAG EOD operations.

VIKING LOW-PROFILE EXHAUST VALVE

Has the same functionality as the standard exhaust valve but with a different design. Fitted as standard on Viking COMBAT and PROTECH.

VIKING X2 EXHAUST VALVE

Developed to meet the increased safety demand of divers who dive in contaminated – or potentially contaminated – water. Built in a chemical resistant plastic material, PC/PBT and equipped with double check valves to minimize the risk of microleakage, which could harm an exposed diver.

Also available in a non-magnetic all black version fulfilling the requirements according to STANAG EOD operations.

HOSE FOR VIKING INLET VALVES

Low pressure hose, length 75 cm, which is delivered with every Viking suit. Also available in a non-magnetic all black version fulfilling the requirements according to STANAG EOD operations.

CHEMICAL PROTECTION FOR EXHAUST VALVES

The Viking Chemical Protection is an add-on item for contaminated water diving, preventing potentially dangerous microleakage via the exhaust valve. Made from an outer shield of Viton®/Butyl rubber with an inner bag containing a chemical absorbent. It is mounted directly to the back of the valve before the valve is mounted onto the suit.

* & ™ are trademarks owned by Ansell Limited or one of its affiliates. © 2013 Ansell Limited. All Rights Reserved.